

氧化磁鐵標準性能表  
Standard Performance Table of Ferrite Magnet

序號 No	產品代號 Model	殘留磁束密度 Residual flux density (Br)		保磁力 Coercive force (bHc)		保磁力 Coercive force (iHc)		最大能量積 Energy product (BH)max		密度 Density (d)	用途 Application
		G	mT	Oe	kA/m	Oe	kA/m	MGOe	kJ/m <sup>3</sup>	g/cm <sup>3</sup>	
1	TG-1B	4000~4100	400~410	1900~2200	151~175	/	/	3.6~4.1	28.6~32.6	4.7~5.0	揚聲器 Speaker
2	TG-1BB	3800~4000	380~400	2200~2600	175~207			3.4~4.0	27.1~31.8	4.7~5.0	電子機器 Electronic devices
3	TG-2B	3800~4000	380~400	2800~3400	223~271			3.4~4.0	27.1~31.8	4.7~4.9	馬達 Motor
4	TG-2BA	4100~4400	410~440	2200~2600	175~206			4.1~4.4	32.6~35.0	4.7~5.0	揚聲器 Speaker
5	TG-2BB	4100~4300	410~430	2700~3200	214~255			4.0~4.4	31.5~34.7	4.7~5.0	揚聲器 Speaker
6	TG-2BC	3400~3800	340~380	≥3200	≥255	≥3900	≥310	2.7~3.4	21.5~27.1	4.6~4.8	馬達 Motor
7	TG-2BD	3800~4100	380~410	3100~3500	246~279	≥3400	≥270	3.4~4.0	27.1~31.6	4.8~5.0	馬達 Motor
8	TG-2BE	3700~4000	370~400	3300~3800	262~303	≥3900	≥310	3.2~3.8	25.6~30.0	4.8~5.0	馬達 Motor
9	TG-2BF	3600~3900	360~390	3100~3500	246~279	≥4800	≥381	3.0~3.6	24.3~28.5	4.8~5.0	馬達 Motor
10	TG-5BB	4200~4400	420~440	2700~3000	214~239	≥2700	≥214	4.2~4.6	33.1~36.3	4.8~5.0	馬達 Motor
11	TG-5BD	4000~4200	400~420	3200~3700	254~294	≥3400	≥270	3.8~4.2	30.2~33.4	4.8~5.0	馬達 Motor
12	TG-5BE	3900~4100	390~410	3500~4000	278~318	≥3900	≥310	3.6~4.0	28.6~31.8	4.8~5.0	馬達 Motor
13	TG-5BF	3800~4000	380~400	3400~3900	270~310	≥4300	≥342	3.4~3.8	27.0~30.2	4.8~5.0	馬達 Motor
14	TG-6BB	4200~4400	420~440	2900~3300	230~263	≥3000	≥238	4.2~4.6	33.1~36.3	4.8~5.0	馬達 Motor
15	TG-6BD	4100~4300	410~430	3100~3600	246~286	≥3400	≥270	4.0~4.4	31.8~35.0	4.8~5.0	馬達 Motor
16	TG-6BE	4000~4200	400~420	3500~4000	278~318	≥3900	≥310	3.8~4.2	30.2~33.4	4.8~5.0	馬達 Motor
17	TG-6BF	3900~4100	390~410	3400~3900	270~310	≥4300	≥342	3.6~4.0	28.6~31.8	4.8~5.0	馬達 Motor
18	TG-7BB	4300~4500	430~450	2900~3300	230~263	≥3000	≥238	4.4~4.8	34.7~38.0	4.8~5.0	馬達 Motor
19	TG-7BD	4200~4400	420~440	3200~3700	254~294	≥3400	≥270	4.2~4.6	33.4~36.6	4.8~5.0	馬達 Motor
20	TG-7BE	4100~4300	410~430	3600~4100	286~326	≥3900	≥310	4.0~4.4	31.8~35.0	4.8~5.0	馬達 Motor
21	TG-7BF	4000~4200	400~420	3500~4000	278~318	≥4300	≥342	3.8~4.2	30.2~33.4	4.8~5.0	馬達 Motor
22	TG-9BD	4400~4600	440~460	3300~3800	262~302	≥3600	≥286	4.6~5.0	36.6~39.7	4.9~5.1	馬達 Motor
23	TG-9BE	4300~4500	430~450	3900~4400	310~350	≥4200	≥334	4.4~4.8	35.0~38.1	4.9~5.1	馬達 Motor
24	TG-9BF	4200~4400	420~440	3800~4300	302~342	≥4700	≥374	4.2~4.6	33.4~36.6	4.9~5.1	馬達 Motor